



°CRYO Arctic

VS

°CRYO Glacier

°CRYO Arctic

°CRYO Glacier

COOLING TECHNOLOGY	→	GAS <i>Indirect injection of liquid nitrogen is used to cool down breathable air</i>	ELECTRIC <i>High-efficiency cooling system with a 2 stage cascade freezer, cools down breathable air</i>
INTERNAL ATMOSPHERE	→	Breathable air	Breathable air
TEMPERATURE PARAMETERS	→	-110°C/166°F down to -140°C/-220°F	-110°C/166°F down to -140°C/-220°F
WHOLE BODY CRYOTHERAPY	→	Yes	Yes
PARTIAL BODY CRYOTHERAPY	→	Yes	No
PRIVATE MODE	→	No	Yes
AUTOMATIC DOOR	→	No	Yes
NUMBER OF ELEMENTS	→	1	3
WEIGHT	→	390kg + Nitrogen tank	600kg cryochamber + 900kg machinery + 160 kg water cooling module
COOLING TIME ON START UP	→	3 minutes	90 minutes
COOLING TIME BETWEEN SESSIONS	→	2 minutes	7 minutes
NUMBER OF MENU PROTOCOLS	→	4	6
SELF OPERATING SYSTEM	→	No <i>A trained operator must be present to manage the machine</i>	Yes <i>Enabling users autonomous treatment capabilities</i>
REMOTE SERVICE	→	Yes	Yes
SPACE REQUIRED	→	Whole unit is located in the one room with additional space required for a nitrogen tank and exhaust system	Recommended additional room for machinery module, and the cooling module is to be installed outdoors
POWER SUPPLY	→	Standard power supply	Custom power supply
	EU	US	EU
	1,5kW 1 phase, 230V 50Hz 15A	1,5kW 1 phase, 120V 60Hz 15A	30kW 3 phase, 400V 50-60Hz 63A
			US
			30kW 3 phase, 208V 60Hz 125A